Journal of educational equipment: Applied research, Volume 2, Issue 321 (September 2024)
ISSN 1859 - 0810

Iot applications of image processing techniques to determine the lane in autonomous driving technology

Le Mai Nam*

**Faculty of Information Technology - East Asia University of Technology*
Received: 7/9/2024; Accepted: 12/9/2024; Published:20/9/2024

Abstract: *Self-driving vehicles are advanced systems designed to function and navigate independently, without the need for human intervention. They possess the ability to sense and assess their surrounding environment, allowing them to make informed decisions to travel to their destination in a consistent and secure way. This paper highlights that one of the key applications of image processing technology in autonomous vehicles is lane detection and tracking. By utilizing cameras, these vehicles can recognize and interpret lane markings, enabling them to adjust their path accordingly to ensure safe and efficient movement.*

Keywords: *Autonomous cars, lane detection, image processing, autonomous driving.*

1. Introduction

The image processing system plays a vital role in the functioning of a self-driving vehicle. It allows the car to recognize and detect objects within its surroundings, assess them, and react accordingly. The process begins with capturing images using the vehicle's onboard camera. These images are then converted into digital data and undergo several processing steps to identify objects, determine their positions, and analyze their movements.

In image processing, detecting and analyzing images demands fast and accurate data processing capabilities. Several techniques are utilized for lane detection, including the H-maxima and Hough transform methods [1], B-snake [2], neural network models [3], [4], and detection algorithms tailored for Raspberry Pi [5], among others. Implementing these approaches requires a solid understanding of image processing and the ability to apply that knowledge effectively in practical scenarios. Each method has its own advantages and limitations, and selecting the appropriate technique depends on the specific needs of the application and the conditions in the real world.

The research in [1] introduces the H-maxima technique, which aims to identify significant local maxima in an image by applying an h-threshold to preserve key points while minimizing or eliminating noise. This method enhances the prominence of important features, improving object recognition and classification. However, effective use of the H-maxima method requires thorough image preparation and preprocessing, which demands a strong understanding of image processing to achieve optimal results.

The B-snake method, also known as Biased-Snake, is employed in the study [2][6] to form an active contour based on reference points, referred to as 'snakes.' This technique is adaptable and can be applied to a wide range of objects, enhancing the model's flexibility and usability. However, the initial setup of the contour and the fine-tuning of parameters—such as curve stiffness, self-energy coefficient, and data coefficient during the optimization process—are essential for achieving optimal performance.

The study focuses on lane detection by integrating image processing and computer vision techniques with onboard vehicle cameras. This approach provides a straightforward and efficient solution for lane recognition, addressing the shortcomings of other methods by eliminating the need for initializations, which reduces errors caused by poor setup. The aim of the research is to develop a practical, simple, and reliable method to assist vehicles in maintaining their lanes. By leveraging cameras alongside image processing and computer vision, the method seeks to lower costs and enhance flexibility, making it suitable for deployment across various vehicle types without relying on complex sensors or costly GPS systems

2. Algorithm description

This section outlines the fundamental steps involved in lane detection and the commonly employed algorithms used in this process.

2.1. The Canny Edge Detection Algorithm

Canny Edge Detection is one of the most widely used techniques for identifying edges in image processing. Introduced by John F. Canny in 1986, it has since become a key tool in both computer vision and image processing applications. The Canny Edge Detection method typically involves the following four steps:

Step 1: Gaussian Smoothing: The input image is convolved with a Gaussian filter to reduce noise and unwanted details.

The process of applying Gaussian blur begins with determining the value of k for the kernel. The size of the kernel $(2k + 1) \times (2k + 1)$, will impact the level of blurriness in the image after application. Subsequently, each pixel in the matrix will be recalculated based on the values of surrounding pixels using the Gaussian equation:

$$H_{ij} = \frac{1}{2\pi\sigma^2}\exp\left(-\frac{\left(1-(k+1)\right)^2+\left(j-(k+1)^2\right)}{2\sigma^2}\right);1\le i,j\le(2k+1) \quad (1)$$

Step 2: Gradient Calculation: After smoothing the image, this step will compute the magnitude and direction of the image's derivative in the horizontal and vertical directions using the Sobel gradient filter. By using the Sobel kernels K_x and K_y, we can calculate the image derivatives G_x and G_y:

$$K_x = \begin{pmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{pmatrix}, K_y = \begin{pmatrix} 1 & 2 & 1 \\ 0 & 0 & 0 \\ -1 & -2 & 1 \end{pmatrix}$$

From the calculated partial derivatives in the x and y directions on the input image, we can compute the gradient magnitude and orientation of each pixel using the following formula:

$$G = \sqrt{G_x^2 + G_y^2}, \quad (2)$$

and

$$\theta(x,y) = \arctan\left(\frac{G_y}{G_x}\right) \quad (3)$$

The terms G and θ are referred to as the magnitude and direction of the gradient.

Step 3: Non-maximum Suppression: Once the magnitude and direction of the derivative have been computed, this step focuses on eliminating non-edge pixels. It does so by comparing the magnitude of each pixel with its neighbors in the direction of the derivative. Pixels that are not local maxima will be discarded, resulting in an image that contains only the edge pixels.

Step 4: Hysteresis Thresholding: Finally, the system employs a two-level thresholding technique to filter out insignificant points and identify strong and weak edge points. The high threshold is effective in eliminating weak points, while the low threshold aids in linking strong points together to form continuous edge boundaries.

2.2. Masking

In image processing, utilizing a Region of Interest (ROI) is essential for concentrating on the key areas of an image while discarding irrelevant parts, thus enhancing processing performance and reducing the effects of noise. ROIs can be defined in various shapes, including circles, squares, triangles, and parallelograms, depending on the specific needs of the task. In this study, we employ a triangular ROI, with the central point of the image serving as the triangle's vertex and two extreme points at the bottom of the image forming the base.

3. Testing

This section evaluates the model's effectiveness in lane detection across different road types and environmental conditions. We specifically tested the model on various surfaces, including typical roads, curved roads, straight roads, standard roads, and highways. Additionally, our experiments were carried out under diverse weather conditions, such as sunny, cloudy, nighttime, shadowy, and rainy scenarios.

In Fig 2.1, we can see that the model exhibits a fairly high and consistent lane detection ability across a variety of environments. However, some limitations still need to be addressed. Specifically, the presence of noisy straight lines within the ROI has resulted in the detection of unnecessary straight lines, which could lead to misunderstandings and adversely affect the model's decision-making. Moreover, accurately detecting curved lanes remains a challenge, which can introduce biases in control and prediction, particularly in complex situations. Additionally, many lanes are still missed, rendering lane detection in low-light conditions unreliable. This oversight of critical details while driving could pose safety risks.

These experiments provided valuable insights to improve and optimize the performance of the lane detection program by enabling us to assess the model's adaptability to various real-world

scenarios. The results of these tests will deepen our understanding of the model's sensitivity, accuracy, and reliability in recognizing and detecting lanes in actual environments.

Fig 2.1. Road lane detection in different scenes

4. Conclusion

This paper highlights the significance of real-time lane detection in intelligent transportation systems. Lane detection has been extensively studied, and we consider lanes as straight lines as long as they fall within a safe range for vehicles, given that they typically consist of long, smooth curves. The lanes were identified using a constrained search region combined with the Hough transformation. The proposed lane recognition technique is effective on both painted and unpainted roads, as well as on straight and slightly curved paths.

In the near future, further efforts should be made to enhance performance under various environmental conditions, such as sunny, foggy, and rainy days.

References

[1]. Ghazali, K., Xiao, R. and Ma, J., (2012), September. *Road lane detection using H-maxima and improved hough transform. In 2012 Fourth International Conference on Computational Intelligence*, Modelling and Simulation (pp. 205-208). IEEE.

[2]. Wang, Y., Teoh, E. K., & Shen, D. (2004). *Lane detection and tracking using B-Snake*. Image and Vision computing, 22(4), 269-280.

[3]. Banskota, N., Alsadoon, A., Prasad, P. W. C., Dawoud, A., Rashid, T. A., & Alsadoon, O. H. (2023). *A novel enhanced convolution neural network with extreme learning machine: facial emotional recognition in psychology practices*. Multimedia Tools and Applications, 82(5), 6479-6503.

[4]. Yalabaka, S., Prasad, C. R., Sanjana, P., Lokesh, B., Shradha, T., & Samala, S. (2022, December). *Lane Detection using Deep Learning Techniques. In 2022 8th International Conference on Signal Processing and Communication (ICSC)* (pp. 412-416). IEEE.

[5]. Chetan, N. B., Gong, J., Zhou, H., Bi, D., Lan, J., & Qie, L. (2020, January). *An overview of recent progress of lane detection for autonomous driving*. In 2019 6th International conference on dependable systems and their applications (DSA) (pp. 341-346). IEEE.

[6]. Kaushal, Rajanish Kumar, R. Arvind, Kshama KB Giri, M. Sindhu, L. Natrayan, and Bindu Ronald. "Deep Learning based Segmentation Approach for Automatic Lane Detection in Autonomous Vehicle." In 2023 International Conference on Self Sustainable Artificial Intelligence Systems (ICSSAS), pp. 268-273. IEEE, 2023.